

Site Report

Report Name Smith Home

Report Date 3/2/2009 3:06:37 PM

Declination -14d 59m

Location HILLSBORO, NH, Zipcode: 03244

Lat/Long 43.123 / -71.914

Weather Station CONCORD, NH, Elevation: 344 Feet

Site distance 22 Miles

Report Type Thermal

Array Type Fixed
Tilt Angle 43.12 deg
Ideal Tilt Angle 43.12 deg
Azimuth 180.00 deg
Ideal Azimuth 180.00 deg

Collector Make American Solar Works

Collector Model ASW52B

Collector Area 26.5 Sq. Feet

Collector Count 4

Total Collector Area 106.2 Sq. Feet

Solar Fraction 0.72

Annual Production 11.5 Million BTU
Propane Cost \$2.78 per gallon
Propane Saved 125.31 gallons

Collector Fluid Water

Layout Configuration SinglePicture

Layout Point Count 1


Notes: Site Analysis for Thermal install

Report generated by SolarPathfinder Assistant Version 4.0.16.0. http://www.solarpathfinder.com

Page: 1/6

System Picture Layout

Layout Type Single Picture Layout Point Count 1



Report generated by SolarPathfinder Assistant Version 4.0.16.0. http://www.solarpathfinder.com Page: 2/6



Thermal Energy Cost Savings

Energy Source Used to Heat Water

Energy Source Propane

Energy Cost \$2.78 per gallon Total Propane Saved 125.31 gallons

Estimated Monthly Savings

| January | \$24.98 |
|-----------|---------|
| February | \$26.46 |
| March | \$30.97 |
| April | \$32.45 |
| May | \$34.18 |
| June | \$33.51 |
| July | \$35.83 |
| August | \$35.50 |
| September | \$30.81 |
| October | \$25.73 |
| November | \$19.77 |
| December | \$18.17 |

Annual Savings \$348.36

Notes: Site Analysis for Thermal install

Report generated by SolarPathfinder Assistant Version 4.0.16.0. http://www.solarpathfinder.com

Page: 3/6



Thermal Data Input Assumptions

Estimated Average Daily Hot Water Usage (gallons/day)

| January | 59.45 |
|-----------|-------|
| February | 59.45 |
| March | 59.45 |
| April | 59.45 |
| May | 59.45 |
| June | 59.45 |
| July | 59.45 |
| August | 59.45 |
| September | 59.45 |
| October | 59.45 |
| November | 59.45 |
| December | 59.45 |

Other Assumptions

Tank Temperature134.96 °FWater Supply Temperature55.04 °FMain Tank Volume100 GallonsSecondary Tank Volume0 GallonsHeat Exchanger Efficiency70.00 %

Notes: Site Analysis for Thermal install

Report generated by SolarPathfinder Assistant Version 4.0.16.0. http://www.solarpathfinder.com

Page: 4/6

Solar Site Analysis Report






Image File SPA_sample.jpg

Solar Obstruction Data

| Month | Unshaded % of Ideal Site Azimuth=180 Tilt=43.12 | Actual Solar Rad w/ Shading Azimuth=180.0 Tilt=43.12 KWH/m ² /day | Solar Hot Water Actual Cost Savings Propane \$2.78/gallon | Solar Hot Water Solar Fraction Azimuth=180.0 Tilt=43.12 | Solar Hot Water Produced Azimuth=180.0 Tilt=43.12 MMBTU | Solar Hot Water Demand Azimuth=180.0 Tilt=43.12 MMBTU |
|-----------|--|--|---|--|---|---|
| January | 95.00% | 3.61 | \$24.98 | 0.61 | 0.8 | 1.4 |
| February | 94.00% | 4.29 | \$26.46 | 0.71 | 0.9 | 1.2 |
| March | 93.00% | 4.53 | \$30.97 | 0.75 | 1.0 | 1.4 |
| April | 96.00% | 4.91 | \$32.45 | 0.81 | 1.1 | 1.3 |
| May | 94.00% | 4.96 | \$34.18 | 0.83 | 1.1 | 1.4 |
| June | 94.00% | 5.01 | \$33.51 | 0.84 | 1.1 | 1.3 |
| July | 94.00% | 5.21 | \$35.83 | 0.87 | 1.2 | 1.4 |
| August | 95.00% | 5.16 | \$35.50 | 0.86 | 1.2 | 1.4 |
| September | 93.00% | 4.52 | \$30.81 | 0.77 | 1.0 | 1.3 |
| October | 91.00% | 3.59 | \$25.73 | 0.62 | 0.8 | 1.4 |
| November | 93.00% | 2.88 | \$19.77 | 0.50 | 0.7 | 1.3 |
| December | 92.00% | 2.63 | \$18.17 | 0.44 | 0.6 | 1.4 |
| Totals | 93.82% | 51.28 | \$348.36 | 0.72 | 11.5 | 16.0 |
| | Unweighted | Effect: 92.76% | | | | |
| | Yearly Avg | Sun Hrs: 4.27 | | | | |

Notes: [None]



Report generated by SolarPathfinder Assistant Version 4.0.16.0. http://www.solarpathfinder.com Page: 5/6

Summary Report

Solar Obstruction Data

| Month | Unshaded % of Ideal Site Azimuth=180 Tilt=43.12 | Actual Solar Rad w/ Shading Azimuth=180.0 Tilt=43.12 KWH/m ² /day | Solar Hot Water Actual Cost Savings Propane \$2.78/gallon | Solar Hot Water Solar Fraction Azimuth=180.0 Tilt=43.12 | Solar Hot Water Produced Azimuth=180.0 Tilt=43.12 MMBTU | Solar Hot Water Demand Azimuth=180.0 Tilt=43.12 MMBTU |
|-----------|---|--|---|--|---|---|
| January | 95.00% | 3.61 | \$24.98 | 0.61 | 0.8 | 1.4 |
| February | 94.00% | 4.29 | \$26.46 | 0.71 | 0.9 | 1.2 |
| March | 93.00% | 4.53 | \$30.97 | 0.75 | 1.0 | 1.4 |
| April | 96.00% | 4.91 | \$32.45 | 0.81 | 1.1 | 1.3 |
| May | 94.00% | 4.96 | \$34.18 | 0.83 | 1.1 | 1.4 |
| June | 94.00% | 5.01 | \$33.51 | 0.84 | 1.1 | 1.3 |
| July | 94.00% | 5.21 | \$35.83 | 0.87 | 1.2 | 1.4 |
| August | 95.00% | 5.16 | \$35.50 | 0.86 | 1.2 | 1.4 |
| September | 93.00% | 4.52 | \$30.81 | 0.77 | 1.0 | 1.3 |
| October | 91.00% | 3.59 | \$25.73 | 0.62 | 0.8 | 1.4 |
| November | 93.00% | 2.88 | \$19.77 | 0.50 | 0.7 | 1.3 |
| December | 92.00% | 2.63 | \$18.17 | 0.44 | 0.6 | 1.4 |
| Totals | 93.67% | 51.28 | \$348.36 | 0.72 | 11.5 | 16.0 |
| | Unweighted | Effect: 92.76% | | | | |
| | Vaarly Aye | Cum Heat 4 20 | | | | |

Yearly Avg Sun Hrs: 4.28
Notes: Site Analysis for Thermal install

Report generated by SolarPathfinder Assistant Version 4.0.16.0. http://www.solarpathfinder.com

Page: 6/6